



Schauer 3210 Wasson Road Cincinnati, Ohio 45209

1-800-899-VOLT (8658) Fax: 1-513-791-7192 www.battery-chargers.com

MODEL JAC2036H, JAC1742H, JAC1548H, JAC1372H, JAC4024H

Fully Automatic Multimode Electronic Charger



Intelligent chargers follow battery impedance to end of charge cycle for all battery types. Fully automatic.

Red LED indicates AC power on, yellow LED indicates battery is charging, green LED indicates float mode.

Charge control: constant current charge to a constant voltage, then to a float standby voltage.

• Current limiting.

- Fully automatic 3 stage charger can be left on the battery in maintaining/float mode.
- Can be set for any type lead acid battery, including conventional, maintenance free, deep cycle, gelled-type, valve regulated batteries.
- Cyclic Voltage: Flooded 2.47 volts/cell; Gel & AGM 2.4 volts/cell. May be preset to customer's specification for battery type.
- Not intended for use as a DC power supply.
- Continuous 100% duty cycle.
- Low voltage start: will start charging a deeply discharged battery with low terminal voltage.

Model JAC2036H Shown

- Reverse polarity and short circuit proof.
- Aluminum case.
- AC Input 115/230 volts, 50 or 60Hz Input voltage autosensed.

JAC4024H	40 AMPS	24 VOLTS	<mark>8"</mark> w x 7.5"н x 6.5"d	13 lbs.
JAC2036H	20 AMPS	36 VOLTS	<mark>8"w x 7.5"н x 6.5"</mark> d	13 lbs.
JAC1742H	17 AMPS	42 VOLTS	<mark>8"w x 7.5</mark> "н x 6.5"d	13 lbs.
JAC1548H	15 AMPS	48 VOLTS	<mark>8"</mark> w x 7.5"н x 6.5"d	13 lbs.
JAC1372	13 AMPS	72 VOLTS	8" w x 7.5"н x 6.5"р	13 lbs.
NOTE: Specify DC connector with order.				

See inside back cover for power equipment adapters

NOTE: Chargers available for other currents and voltages, contact factory.