Schauer Battery Chargers

MOBILITY CHARGERS W/ 3-PIN XLR - LEAD ACID

MODELS: JAC0324-XLR, 3 AMP 24 VOLT

JAC0524-XLR, 5 AMP 24 VOLT

JAC0724-XLR, 7 AMP 24 VOLT



FEATURES

Cooling Fan
Reverse Polarity Protection
High Energy Efficiency (UEC, BC)
Voltage Limited
Current Limited
Over Voltage Protection
Over Temperature Protection
Short Circuit Protection
Aluminum Case
Mounting Flanges
On / Off Switch
Detachable AC Cord, 5 ft (NEMA 5-15/IEC C13)
Two-year Limited Warranty

www.battery-chargers.com
513-791-3030 x1

Description

24 Volt – 3, 5, 7 Amp
Automatic Switch Mode Charger with Float Mode
Dimensions (LxWxH):
178 x 88 x 47 mm
Weight:
0.8 kg
AC Input:
Input Voltage: 115 VAC, 50/60 Hz
Input Current Max: 3.2 Amps
Single Phase
Input Receptacle: IEC C14
DC Output:
Output Voltage - Nominal: 24 VDC
Output Voltage - Bulk / Cyclic Voltage: 28.8 VDC
Float Voltage: 26.6 VDC
Max DC Current: 3, 5, 7 Amps
Battery Type: Lead Acid, AGM, Gel Stage Charging Profile: CC/CV/Float